



# MACHINE PRECISION AXLE CORP.



6002-2RSLTN9/C3VT162 Bearing 2D drawings and 3D CAD models

## SKF 6002-2RSLTN9/C3VT162 Single Row Ball Bearings

Bearing No. 6002-2RSLTN9/C3VT162

Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.033
EAN	7316571821481
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Polyamide
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 9MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C3-Loose Internal Clearance; Polyamide Cage
Other Features	Deep Groove   Low Friction   NBR Seal   Prelubricated



## MACHINE PRECISION AXLE CORP.

Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6002-2RSLTN9/C3VT162
Weight / LBS	0.03
D	1.26 Inch   32 Millimeter
Inner Race Width	0 Inch   0 Millimeter
d	0.591 Inch   15 Millimeter
Outer Race Width	0.354 Inch   9 Millimeter
bore diameter:	15 mm
static load capacity:	2.85 kN
outside diameter:	32 mm
precision rating:	Not Rated
overall width:	9 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Fiberglass Reinforced Nylon
closure type:	Double Sealed
outer ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
internal clearance:	C3
maximum rpm:	26000 RPM
operating temperature range:	-40 to +210 ° F
series:	60
dynamic load capacity:	5.85 kN